

# USB 2.0 A with Booster to USB 2.0 B Panel Mount Cable, F-F



#### Item no. FSP1041

### **Specification:**

· Connector 1: USB 2.0 Type-A female with Booster

· Connector 2: USB 2.0 Type-B female with screw locking

Gold plated contact, Nickel plated shellNut and Screw type: M3 nickel plated

Hole Pitch: 27±0.5mm

Cable Conductor: Bare Copper

Wire Gauge: 28/24AWG

• Outer diameter: 4.5±0.2mm

· Shielding: Aluminum foil, Braiding

· Housing: ABS Shell

Jacket: PVC

· Support high speed USB 2.0 devices and the transfer rate reaches to 480Mbps

Backward compliant with full-speed USB 1.1 (12 Mbps) and low speed USB 1.0 (1.5 Mbps)

· Compliance: RoHS, REACH

#### **Order Information:**

• FSP1041: USB 2.0 A female with IC to B female Panel Mount Cable, 0.3m, 28AWG, OD4.5  $\pm$  0.2mm

## **Description:**

Farsince High Quality USB 2.0 A Female with Booster to B Female Panel Mount Cable is the perfect solution for combining USB Type-A and USB Type-B cables to achieve connectivity through a panel. This allows the user to provide connectivity from a source that is contained within a secure location. USB 2.0 A with Booster to USB 2.0 B Panel Mount Cable is short and designed for minimal signal loss.

It provides a transfer rate up to 480Mbps depending upon the peripheral's USB version, and easily attaches to any USB device. Flexible PVC jacket, Foil and braid shielding, and the twisted pair construction make a better performance. Chip design can provide long distance data transmission.