

## USB 3.0 A male to female Panel Mount Extension Cable



### Description:

Our cable is designed to seamlessly link two USB cables for optimal connectivity through a panel. This arrangement enables you to establish a connection from a secure location source. Built with precision, the short cable ensures minimal signal loss. It boasts a transfer rate of up to 5 Gbps, subject to the peripheral's USB version, and offers effortless attachment to any USB device. It also possesses foil and braid shielding that safeguard against EMI/RFI interference, while its twisted pair design minimizes crosstalk, ensuring high-speed and error-free data transfer.

### Item no. FSP1061

### Specification:

- Connector 1: USB 3.0 A male
- Connector 2: USB 3.0 A female with screw locking
- Gold plated contact, Nickel plated shell
- Nut and Screw type: M3 nickel plated
- Hole Pitch:  $30 \pm 0.5$ mm
- Cable Conductor: Bare Copper
- Wire Gauge: 28/28/24AWG
- Outer diameter:  $5.5 \pm 0.15$ mm
- Shielding: Aluminum foil, Braiding
- Housing: Injection molding
- Jacket: PVC
- Support super speed USB 3.0 devices and the transfer rate reaches to 5 Gbps
- Backward compliant with high-speed USB 2.0 (480Mbps)
- Compliance: RoHS, REACH

### Order Informaiton:

- FSP1061: USB 3.0 A male to female Panel Mount Extension Cable, 0.3m, 28AWG, OD $5.5 \pm 0.15$ mm